

# FLIP-X 简易选型表

类型	尺寸 (mm)	导距 (mm)	最大搬运重量 (kg)		最高速度 (mm/sec)	行程 (mm)	型号	页码
			水平	垂直				
T 型 无框架结构机型	W45×H53	12	4.5	1.2	720	50~300	T4/T4H	T4: <a href="#">P064</a>
		6	6	2.4	360			T4H: <a href="#">P065</a>
		2		7.2	120			
	W55×H52	20	3	—	1200	50~800	T5/T5H	T5: <a href="#">P066</a>
		12	5	1.2	800	50~600		T5H: <a href="#">P067</a>
		6	9	2.4	400			
	W65×H56	20	10	—	1333	50~800	T6	<a href="#">P068</a>
		12	12	4	800	50~600		
		6	30	8	400			
	W94×H98	30	15	—	1800	150~1050	T9 (标准)	<a href="#">P069</a>
		20	30	4	1200			
		10	55	10	600			
		5	80	20	300			
		30	25	—	1800	150~1050	T9H (高推力)	<a href="#">P070</a>
		20	40	8	1200			
10		80	20	600				
5		100	30	300				
F 型 带高刚度框架机型	W80×H65	20	12	—	1200	150~800	F8	<a href="#">P071</a>
		12	20	4	720			
		6	40	8	360			
	W80×H65	30	7	—	1800	150~1050	F8L	<a href="#">P072</a>
		20	20	4	1200			
		10	40	8	600			
		5	50	16	300			
	W80×H65	20	30	—	1200	150~1050	F8LH	<a href="#">P074</a>
		10	60	—	600			
		5	80	—	300			
	W110×H71	30	15	—	1800	150~1050	F10	<a href="#">P075</a>
		20	20	4	1200			
		10	40	10	600			
		5	60	20	300			
	W136×H83	30	15	—	1800	150~1050	F14 (标准)	<a href="#">P076</a>
		20	30	4	1200			
		10	55	10	600		F14H (高推力)	<a href="#">P077</a>
		5	80	20	300			
	W168×H100	50	50	10	2200	1100~2050	F17L	<a href="#">P080</a>
		40	40	—	2400	200~1450		
		20	80	15	1200	200~1250	F17	<a href="#">P078</a>
10		120	35	600				
W202×H115	40	60	—	2400	200~1450	F20	<a href="#">P082</a>	
	20	120	25	1200				
	10	—	45	600				
W202×H120	20	80	—	1200	1150~2050	F20N	<a href="#">P084</a>	
N 型 螺栓旋转机型	W145×H120	20	50	—	1200	500~2000	N15 (单载型)	<a href="#">P086</a>
				—		250~1750	N15D (双载型)	<a href="#">P088</a>
	W180×H115		80	—		500~2500	N18 (单载型)	<a href="#">P090</a>
				—		250~2250	N18D (双载型)	<a href="#">P092</a>
B 型 同步带驱动机型	W100×H81	带驱动	10	—	1875	150~2550	B10	<a href="#">P094</a>
	W146×H94	带驱动	20	—	1875	150~3050	B14 (标准)	<a href="#">P096</a>
30			—	B14H (高推力)			<a href="#">P098</a>	
YMS 型 拉杆式机型	—	12	4.5	1	600	50~200	YMS45	<a href="#">P100</a>
		6	6	2	300			
—	—	12	5	1.5	600	50~300	YMS55	<a href="#">P101</a>
		6	9	4	300			
R 型 旋转轴机型	—	—	0.12kgm <sup>2</sup>	—	360°/sec	360°	R5	<a href="#">P102</a>
			0.36kgm <sup>2</sup>	—			R10	<a href="#">P103</a>
			1.83kgm <sup>2</sup>	—			R20	<a href="#">P104</a>

※ 尺寸约为主机截面的最大外形尺寸。